

SUNNY TRIPOWER 3.0 / 4.0 / 5.0 / 6.0

With SMA SMART CONNECTED



STP3.0-3AV-40 / STP4.0-3AV-40 / STP5.0-3AV-40 / STP6.0-3AV-40



Intelligent service with
SMA Smart Connected

Compact

- One-person installation due to low weight of 17 kg
- Compact design means minimum space requirements

Intelligent

- 100% plug and play installation
- Automated service thanks to SMA Smart Connected
- Integrated TS4-R communication

High yields

- Free online monitoring via Sunny Places
- Less power from the grid due to direct use of excess energy

Combinable

- Intelligent energy management and storage solutions can be added anytime
- Can be combined with TS4-R components for module optimization

SUNNY TRIPOWER 3.0 / 4.0 / 5.0 / 6.0

Higher yields for private homes – intelligent solar power generation

The new Sunny Tripower 3.0–6.0 ensures maximum energy yields for private homes. This inverter combines the integrated Service SMA Smart Connected service and intelligent technology for all ambient requirements. Thanks to its extremely light design, the device can be installed quickly and easily. The Sunny Tripower can be commissioned quickly via smartphone or tablet thanks to its integrated web interface. For specific requirements on the roof, such as shading, the TS4-R module optimizers can be added into the system, with all communication and monitoring facilitated through the inverter. Current communication standards make the inverter future-proof, meaning intelligent energy management solutions as well as SMA storage solutions can be flexibly added anytime.

SMA SMART CONNECTED

The integrated service for ease and comfort

SMA Smart Connected* is free monitoring of an inverter via the SMA Sunny Portal. If an inverter fails, SMA proactively informs the PV system owner and the installer. This saves valuable working time and costs.

With SMA Smart Connected, the installer benefits from rapid diagnoses by SMA. They can thus quickly rectify the fault and score points with the customer thanks to the additional, attractive services.



ACTIVATION OF SMA SMART CONNECTED

During registration of the system in the Sunny Portal, the installer activates SMA Smart Connected and benefits from automatic Inverter monitoring by SMA.



AUTOMATIC INVERTER MONITORING

SMA takes on the job of inverter monitoring with SMA Smart Connected. SMA automatically checks the individual inverters for anomalies around the clock during operation. Every customer thus benefits from SMA's many years of experience.



PROACTIVE COMMUNICATION IN THE EVENT OF FAULTS

After a fault has been diagnosed and analyzed, SMA informs the installer and end customer immediately by e-mail. Everyone is thus optimally prepared for the troubleshooting process. This minimizes downtime and saves time and money. Regular power reports also provide valuable information about the overall system.



REPLACEMENT SERVICE

If a replacement device is necessary, SMA automatically supplies a new inverter within one to three days of the fault diagnosis. The installer can contact the PV system operator of their own accord and replace the inverter.




PERFORMANCE SERVICE

The PV system operator can claim compensation from SMA if the replacement inverter is not delivered within three days.

* Details: see document "Description of Services - SMA SMART CONNECTED"

Efficiency curve



● Standard features ○ Optional features — not available
 Data in nominal conditions
 Last revision: June 2018

Technical data	Sunny Tripower 3.0	Sunny Tripower 4.0	Sunny Tripower 5.0	Sunny Tripower 6.0
Input (DC)				
Max. PV array power	6000 Wp	8000 Wp	9000 Wp	9000 Wp
Max. input voltage	850 V	850 V	850 V	850 V
MPP voltage range	140 V to 800 V	175 V to 800 V	215 V to 800 V	260 V to 800 V
Rated input voltage			580 V	
Min. input voltage / initial input voltage			125 V / 150 V	
Max. input current input A / input B			12 A / 12 A	
Max. DC short-circuit current input A / input B			18 A / 18 A	
Number of independent MPP inputs / strings per MPP input			2/A; 1; B: 1	
Output (AC)				
Rated power [at 230 V, 50 Hz]	3000 W	4000 W	5000 W	6000 W
Max. apparent power AC	3000 VA	4000 VA	5000 VA	6000 VA
Nominal AC voltage			3/N/PE, 220 V / 380 V 3/N/PE, 230 V / 400 V 3/N/PE, 240 V / 415 V	
AC voltage range			180 V to 280 V	
AC grid frequency / range			50 Hz / 45 Hz to 55 Hz 60 Hz / 55 Hz to 65 Hz	
Rated grid frequency / rated grid voltage			50 Hz / 230 V	
Max. output current	3 x 4.5 A	3 x 5.8 A	3 x 7.6 A	3 x 9.1 A
Power factor at rated power / Displacement power factor, adjustable			1 / 0.8 overexcited to 0.8 underexcited	
Feed-in phases / connection phases			3 / 3	
Efficiency				
Max. efficiency / European efficiency	98.2% / 96.5%	98.2% / 97.1%	98.2% / 97.4%	98.2% / 97.4%
Protective devices				
Input-side disconnection point			●	
Ground fault monitoring / gnd monitoring			● / ●	
DC reverse polarity protection / AC short circuit current capability / galvanically isolated			● / ● / -	
All-pole-sensitive residual-current monitoring unit			●	
Protection class (according to IEC 62103) / surge category (according to IEC 60664-1)			I / III	
General data				
Dimensions [W / H / D]			435 mm / 470 mm / 176 mm [17.1 inches / 18.5 inches / 6.9 inches]	
Weight			17 kg [37.4 lbs]	
Operating temperature range			-25°C to +60°C [-13°F to +140°F]	
Noise emission, typical			30 dB(A)	
Self-consumption (at night)			5.0 W	
Topology			Transformerless	
Cooling concept			Convection	
Degree of protection (according to IEC 60529)			IP65	
Climatic category (according to IEC 60721-3-4)			4K4H	
Max. permissible value for relative humidity (non-condensing)			100%	
Equipment				
DC connection / AC connection			SUN-VLIIX / AC connector	
Display via smartphone, tablet, laptop			●	
Interfaces: WLAN, Speedwire / Webconnect, TS4-R			● / ● / ●	
Warranty: 5 / 10 / 15 years			● / ○ / ○	
Certificates and permits (more available upon request)			AS 4777, C10/11, CE, CEB 021, DIN EN 62109-1/ IEC 62109-1, DIN EN 62109-2/ IEC 62109-2, EN 50438, G69/3, G83/3, HEN-EN 50438, NRS 097-2-1, OVE / ÖNORM E 8001-4:712, PPDS, PPC, RD 1699, SI 4777, TR 3.2.1, UTE C15-712, VDE AEN 4106, VDE 0126-1-1, VFR 2014	
Certificates and approvals (currently being planned)			DFWA 2016, EN 62116, IEC 61727, IREN 50438, NBR 16149	
Type designation	STP3.0-3AV-40	STP4.0-3AV-40	STP5.0-3AV-40	STP6.0-3AV-40

